

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNELY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

Dept	Qty
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1

REV. DESCRIPTION DRAWN CHECKED APPROVED
A NEW RELEASE WPY 01/12/26'

NOTES:
1. Rated voltage:600V.
2. Rated current:250A.
3. Contact resistance:0.6mΩ Max
4. Dielectric strength:5000V Min
3. Temp. Range:-40℃~+125℃.
4. Protection grade:IP54.
Materials:
1. Contact: Copper Alloy, Ag plated.
2. Insulator: PA66
Product Number Code:
DS1213-01 - X X X X X
Mounting type
A:A type
Contact plating
Y:Silver
Housing color
B:Black(Negative)
E:Orange(Positive)
Connector type
F:Female
Rated current
250:250A

Installation dimensions

(Series Image-Reference Only)

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE
X.	±0.60	X.	±5°	UNITS	mm
.X	±0.38	.X	±3°	SHEET SIZE	A4
.XX	±0.25	.XX	±2°		

DRAWING TYPE	CUSTOMER	SHEET	
SCALE	1:1	1 OF 2	
DRAWING NO.	C-DS1213-01-XXXXX-A		

晨翔电子有限公司
CONNELY CONNELY ELECTRONIC CO. LTD

